

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. *(Currently Amended)* A DC-offset eliminating method for a receiving circuit of a receiver which receives signals comprising a plurality of frames continuously sent to the receiving circuit, each of the frames has a ~~predetermined frame structure and only at the head of each frame~~ a preamble portion is added only at the head of each frame, wherein the method comprises: comprising the steps of:

calculating a DC-offset component depending upon the received signals;

subtracting said DC-offset component from the received signals; and

performing a DC-offset eliminating operation based on the subtracted result, wherein ~~in said DC offset eliminating operation,~~ a DC offset follow-up speed is reduced ~~set for reducing a follow up speed with respect to the DC offset~~ when said preamble portion is being received, regardless of a time when a continuous reception is performed in which all of said frames are received to recognize the timing of the frame number to be received or a time when an intermittent reception is executed in which only a frame destined for said receiver itself is received.

2. *(Currently Amended)* The DC-offset eliminating method according to claim 1, wherein

said frames comprise ~~including as said frame structure,~~ an alignment portion, ~~a control portion~~
~~providing indications of the frame number cyclic at predetermined intervals and of which~~
~~receiver should receive the frame number, a DATA portion,~~ and a signal-end indication portion
showing as to whether other frames continuously follow said frames, and wherein said DC-offset
eliminating operation changes over said DC-offset follow-up speed in accordance with a signal
obtained by the logical AND operation performed on a frame-continuation detection signal
which becomes “1” when said alignment portion is detected from the received frames and
becomes “0” when a signal end contained in said signal-end indication portion is detected, and
on a received frame signal which becomes “1” only when the frames destined for said receiver
itself.

3. (*Original*) The DC-offset eliminating method according to claim 2, wherein said DC-
offset follow-up speed is associated with a predetermined follow-up speed coefficient which
takes one of two values, 0 or a positive value.

4. (*Currently Amended*) A receiving circuit for eliminating a DC offset comprising:
a detecting circuit for selectively receiving and detecting signals configured by a plurality
of frames which are continuously sent to the receiving circuit, each of said frames comprising
~~including~~ an alignment portion, a control portion providing indications of the frame number
cyclic at predetermined intervals and of which receiver should receive the frame number, a
~~DATA portion,~~ and a signal-end indication portion showing as to whether other frames

continuously follow said frames, and ~~at the head of each frame~~ a preamble portion is added at the head of each frame;

an analog to digital (A/D) converting circuit for converting said detected signals into digital signals;

a DC-offset eliminating circuit for eliminating a DC-offset component from said converted digital signals;

a demodulating circuit for demodulating said frames from said digital signals from which the DC-offset component has been eliminated;

a control circuit for determining the frame number and which frames should be received, depending upon information input from said control portion so as to turn on the power to said detecting circuit and said A/D converting circuit, thereby outputting a control signal for instructing to receive an appropriate frame, and for outputting to said DC-offset eliminating circuit a received frame signal showing that said appropriate frame is being received, depending upon information contained in said alignment portion in the received frames; and

an signal-end detecting circuit for outputting a frame-continuation detection signal to said DC-offset eliminating circuit by monitoring said information contained in said alignment portion and information contained in said signal-end indication in the received frames, wherein said DC-offset eliminating circuit comprises: ~~includes:~~

a subtracting circuit for eliminating a DC offset by subtracting a calculated DC-offset value from said digital signals, and for outputting the result to said demodulating circuit;

a multiplying circuit for multiplying said output from said subtracting circuit by a

coefficient H or L ($0 < L < H$);

an adding circuit for adding said calculated DC-offset value to an output from said multiplying circuit;

a 1-bit delay circuit for delaying an output from said adding circuit by one bit to output said calculated DC-offset value; and

an AND circuit for performing logical AND operation on said received frame signal input from said control circuit and said frame-continuation detection signal input from said signal-end detecting circuit,

~~characterized in that:~~

wherein said DC-offset eliminating circuit selects any one of said coefficients H and L depending upon an output from said AND circuit.

5. (*Original*) The receiving circuit according to claim 4, wherein said coefficient L takes the value of 0, and said coefficient H takes the value of 1.